

## Model-ED-563 8 PORT REVERSE POE SWITCH (All Uplink)



### Product Specification

Product description	8 port 100M POE Enhanced fast type Ethernet switch (8 port uplink)
POE Function	REVERSE port1~port8 VOL DC 9-57V
Characteristic	Each port POE signal indicator Curing isolation function Can be used to connect 19 users Onu setup shown below can also be used to connect 49 users(as per speed )
Interface	8port 10/100M- REVERSE POE (all uplink) (All ports support MDI/MDIX adaptive) 1 port DC out 12V MAX 2A(5.5/2.1)
Forwarding mode	Store and forward
network media	10BASE-TX: And more than 5 types of unshielded twisted pair( $\leq 150m$ ) 100BASE-TX: And more than 5 types of unshielded twisted pair( $\leq 150m$ )
Compatible network protocols and standards	IEEE 802.3i 10BASET IEEE 802.3u 100BASETX
LEDs indicator	Each port connection status, the working state of PoE system of the power indicator light
Power support	DCIN:9V-57V or DCOUT:12V MAX 2A

Environmental Standard	Working temperature:0°~55°C Storage temperature:-20°~75°C Working humidity:10%~90%,No condensation Storage humidity:10%~95%,No condensation
------------------------	--

