





Connecting the World





ED-4100 OTDR

- *Event Dead Zone As Lower As 1.5 Meter.
- *Combined Multi Dynamic Range And Wavelengths.
- *Integrated 10 Mw Visual Fault Locator.
- *5.6-inch Outdoor-enhanced Touch Screen.
- *7.4 V /4.4 Ah Lithium Battery.



ED-710

- *Digital & Analog Measurement.
- *Supports Annex A(16, 32, 64, 128 & 256) And (64 & 256) Qam Modes.
- *Full Channel Range (5 Mhz 860 Mhz)

GEPON Products OLT UNO PLC Splitter

"OTHER PRODUCTS"

RF. Products EDFA Optical Transmitter Optical Node

Co-Axial Cable **FTTH Cables** CAT 6 Camera Wire





CATV PRODUCTS



- SUPPORTS BANDWIDTH OF 1535-1565 nm
- RECOMMENDED OPTICAL POWER 0 TO -3 dbm
- MAX OPERATING POWER FOR LASER >500 Mw
- · 4 output of 16 dbm



1550 Optical Transmitter

- (1) Frequency Range: 45~862MHz.
 (2) RF input level; 75dB~85dB.
 (3) With AGC/MGC function, on-line RF control.
 (4)Use high efficient SMPS, power supply: AC60V/220V/DC48



"OTHER PRODUCTS"

GEPON Products OLT **PLC Splitter**

RF. Products **EDFA Optical Transmitter Optical Node**

Co-Axial Cable **FTTH Cables** CAT 5e Camera Wire







Core Fusion Splicer



CORE FUSION SPLICER

- 6 Sec Splicing Time
- 18 Sec Heating Time
- Operating methods Button/Touch screen
- Shock-Proof, Water-Proof, Dust Free
- Electrode Life 5000 Arc

Website: www.eurodigital.in







Arc Fusion Splicer



ARC FUSION SPLICER

- 6-8 sec. splicing time
- 30 sec heating time
- Operating methods Button/Touch screen
- Shock-proof, water-proof
- Automatic ARC calibration by air pressure and temperature

Website: www.eurodigital.in



EURO SIGIAL Connecting the World.....





FTTH CABLE

2, 4, 6, 12 Core (Support & Without Support)

Networking Cable CAT-5, CAT-6



CCTV Camera Wire





GEPON Products
OLT
ONU
PLC Splitter

COAXIAL CABLE RG-6, RG-11, RG-59

"OTHER PRODUCTS"

RF. Products
EDFA
Optical Transmitter
Optical Node

Co-Axial Cable
FTTH Cables
CAT 6
Camera Wire

Website: www.eurodigital.in







OTDR Optical Time Domain Reflectometer



ED-4100 OTDR

- Event Dead Zone as Lower as 1.5 Meter
- Combined Multi Dynamic Range and Wavelength
- Integrated 10 MW Visual Fault Locator
- 5-6 inch Outdoor-enhanced Touch Screen
- 7.4 V / 4.4 Ah Lithium Battery

Website: www.eurodigital.in